



g-Force T/A Drag Radial & Comp T/A Drag Radial

The BFGoodrich g-Force T/A and Comp T/A Drag Radial's are DOT approved street legal drag tires that were developed to meet the needs of the drivers of high performance vehicles by providing race winning traction and control at the strip from a tire that is fully streetable. On the outside the g-Force T/A Drag Radial molds a new tread rubber compound into a 5.0mm deep directional tread design that features massive competition developed tread blocks for quick response and optimized for straight-line grip'



g-Force T/A Drag Radial

Comp T/A Drag Radial

DESCRIPTION Comp T/A Drag Radial	DESCRIPTION g-Force T/A Drag Radial	Price \$AUD	Price \$NZD	Rim Width range inches	Measuring rim	Section width on measuring rim	Overall Diameter	Tread depth (mm)	Max Load (kgs)	Tire Pressure	section width inches	dia inches	max load psi
	215/60 R 14	275	320	5.5 → 7.5	6.5	216	559	5	488	at 44 psi	8.5	22	1074
	225/45 R 14	290	340	7 → 8.5	7.5	221	615	5	531	at 44 psi	8.7	24.2	1168
	205/50 R 15	310	360	5.5 → 7.5	6.5	216	584	5	506	at 44 psi	8.5	23	1113
	205/40 R 17	400	460	7 → 8	7.5	221	597	5	451	at 44 psi	8.7	23.5	992
	225/45 R 17	445	520	7 → 8.5	7.5	234	635	5	601	at 44 psi	9.2	25	1323
	245/40 R 18	680	790	8 → 9.5	8.5	249	650	5	561	at 44 psi	9.8	25.6	1235
235/60 R 15		350	400	6 → 8.5	7.0	241	663	5	751	at 44 psi	9.5	26.1	1653
295/65 R 15		450	510	8 → 10	8.5	315	752	5	1182	at 44 psi	12.4	29.6	2601
345/55 R 15		500	560	10 → 12	11.0	371	757	5	1323	at 44 psi	14.6	29.8	2910
275/40 R17		600	680	9-11	9.5	278	652	5	650	at 44 psi	11	25.7	1433
255/50 R 16		520	580	7 → 9	8.0	262	663	5	767	at 44 psi	10.3	26.1	1687
315/35 R 17		700	790	11 → 12	11.0	315	650	5	651	at 44 psi	12.4	25.6	1433

* Includes relevant GST

EUROPEAN
TECHNIQUE

Australian and New Zealand Motorsport Tyre distributor for Michelin and BFGoodrich Tires.

338 Swan Street Richmond VIC 3121 • Ph: 03 9428 5547
Technical support contact; Trevor Sheumack 0418 548 578

www.tracktyres.com.au