

Pilot Sport Cup

“Proven to be the fastest Targa/Track DOT approved tyre, offering outstanding performance and durability available in sizes from 15” to 19”.

The Pilot Sport Cup uses dual zone tread compounds, the outer shoulder compound optimized for cornering and the inner compound focused on wet road performance. These tread compounds are molded into a 5.0mm deep asymmetric tread design that features a solid outer shoulder block and longitudinal grooves and independent tread blocks on the inner portion.



Internally the Pilot Sport Cup features two, full width steel belts to stiffen the tread area to help prevent the contact patch distorting during aggressive acceleration, cornering and braking. The Pilot Sport Cup has evolved in conjunction with Michelin’s motorsport technology and Pilot Sport line of maximum performance tyres.

DESCRIPTION Pilot Sport Cup	Load/ Speed Rating	Price* \$AUD	Price* \$NZD	Rim Width range inches	Measuring rim	Section width on measuring rim	Overall Diameter	Tread depth (mm)	Max Load (kgs)	
225/50 ZR 15	91Y	325	370	6 > 8	7	226	608	5	615	at 35 psi
205/55 ZR 16	91Y	385	435	5.5 > 7.5	6.5	212	636	5	615	at 35 psi
225/50 ZR 16	92Y	485	550	6 > 8	7	229	637	5	630	at 35 psi
245/45 ZR 16	94Y	475	540	7.5 > 9	8	251	632	5	670	at 35 psi
205/50 ZR 17	89Y	500	565	5.5 > 7.5	7.0	228	638	5	580	at 35 psi
225/45 ZR 17	91Y	525	595	7 > 8.5	7.5	227	637	5	615	at 35 psi
255/40 ZR 17	94Y	550	620	8.5 . 10	9	273	640	5	670	at 35 psi
235/40 ZR 18	91Y	630	710	8 > 9.5	8.5	241	645	5	615	at 35 psi
265/35 ZR 18	93Y	630	710	9 > 10.5	9.5	276	640	5	650	at 35 psi
285/30 ZR 18	93Y	650	735	10 > 11	10	289	638	5	650	at 35 psi
295/30 ZR 18	94Y	740	835	10 > 11.5	11.0	307	640	5	670	at 35 psi
315/30 ZR 18	98Y	830	937	10.5 >	12.11	338	647	5	750	at 35 psi
345/30 ZR 18	104Y	940	1,060	11.5 > 12.5	12.0	358	668	5	900	at 35 psi
235/35 ZR 19	87Y	790	825	8 > 9.5	8.5	241	647	5	545	at 35 psi
265/30 ZR 19	89Y	800	900	9 > 10	9.5	273	642	5	580	at 35 psi
305/30 ZR 19	102Y	960	990	10 > 11.5	11	313	667	5	.	at 35 psi

*Including relevant GST

[Download Printable pdf version](#)